

GRANTT STELLAR 5000 SAE 10W-40



Product Description

GRANTT STELLAR 5000 SAE 10W-40 is a synthetic blend motor oil. The unique additive technology reduces friction and wear at start-up, providing outstanding protection against sludge formation and varnish deposits under the most severe driving conditions.

GRANTT STELLAR 5000 SAE 10W-40 is designed to deliver exceptional thermal and oxidation stability for longer oil drain interval, thus minimizing oil thickening at high operating temperature.

Application	GRANTT STELLAR 5000 SAE 10W-40 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel engine including fuel injected, turbocharged, conventional, multi-valve, naturally aspirated, LPG and NGV engine.
--------------------	--

Benefits	<ul style="list-style-type: none">• Excellent engine wear protection in the most severe driving conditions• Helps prevent dirt and contamination from turning into performance robbing deposits• Maintains engine responsiveness• Excellent thermal and oxidation stability
-----------------	--

Specifications

- API SN/CF

**Typical Properties**

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-40
API Service Category		API SN/CF
Density @30°C, kg/l	ASTM D4052	0.8481
Kinematic Viscosity @40°C, cSt	ASTM D7042	92.4
@100°C, cSt	ASTM D7042	14.5
Viscosity Index	ASTM D2270	162
Flash Point, °C, Min	ASTM D92	216
Pour Point, °C, Min	ASTM D97	-36
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	7.3