

GRANTT QUASAR SAE 10W



Product Description

GRANTT QUASAR SAE 10W is a high quality mono-grade diesel engine oil that provides superior protection which reduces soot formation and offers rust and corrosion protection on critical engine components.

Application	GRANTT QUASAR SAE 10W is suitable for transmission and mobile hydraulic system, heavy duty equipment for construction, mining and agriculture operations.
--------------------	---

Benefits	<ul style="list-style-type: none">• Minimizes engine wear under severe operating conditions.• Maintains engine cleanliness.• Protection against rust and corrosion.
-----------------	---

Specifications

- API CF-4/SG

**Typical Properties**

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W
API Service Category		API CF-4/SG
Density @30°C, kg/l	ASTM D4052	0.8704
Kinematic Viscosity @40°C, cSt	ASTM D7042	36.9
@100°C, cSt	ASTM D7042	6.2
Viscosity Index	ASTM D2270	114
Flash Point, °C, Min	ASTM D92	210
Pour Point, °C, Min	ASTM D97	-27
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	7.7