



Product Description

GRANTT QUASAR SAE 30 is a high quality mono-grade diesel engine oil that provides superior protection against wear, deposits formation, rust and corrosion. It is formulated to deliver outstanding thermal and oxidation stability to maintain engine cleanliness.

Application	GRANTT QUASAR SAE 30 is suitable for heavy duty equipment for construction, mining and agriculture operations.
--------------------	--

Benefits	<ul style="list-style-type: none">• Minimizes soot formation to maintain engine cleanliness.• Protection against rust and corrosion.• Superior thermal and oxidation stability.
-----------------	---

Specifications

- API CF/CF-2/SF



Typical Properties

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 30
API Service Category		API CF/CF-2/SF
Density @30°C, kg/l	ASTM D4052	0.8823
Kinematic Viscosity @40°C, cSt	ASTM D7042	82.4
@100°C, cSt	ASTM D7042	10.1
Viscosity Index	ASTM D2270	102
Flash Point, °C, Min	ASTM D92	210
Pour Point, °C, Min	ASTM D97	-18
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	N/A
Total Base Number, mgKOH/g	ASTM D2896	6.4