

GRANTT QUADRA 4T SAE 10W-40 SYNTHETIC BLEND



Product Description

GRANTT QUADRA 4T SAE 10W-40 is a premium synthetic blend oil designed for four-stroke motorcycle engine oils. Formulated with the advanced additive technology to provide better clutch performance and smoother gear changes even under the most extreme temperatures in high-speed riding conditions.

Enhanced with selected synthetic hydrocarbon base oils and special oil formulation to keep oil viscosity in grade for longer. This oil is developed to deliver ultimate engine cleanliness and wear protection by removing sludge and engine deposits thus helps prolong engine life.

Application	GRANTT QUADRA 4T SAE 10W-40 is suitable for both standard air-cooled and liquid-cooled 4-stroke motorcycles.
--------------------	--------------------------------------------------------------------------------------------------------------

Benefits	<ul style="list-style-type: none">• Optimized wet-clutch performance by reducing excess heat and friction.• Excellent detergency to provide reliable protection, cleanliness and smoother-running engine.• Reliable thermal and shear resistance to prevent oil thickening and piston deposits under high temperature conditions.• Helps prolong engine life.
-----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Specifications

- API SM
- JASO MA2

GRANTT QUADRA 4T SAE 10W-40 SYNTHETIC BLEND



Typical Properties

Test	Method	Typical Results
API Service Category		API SM
Density @30°C, kg/l	ASTM D4052	0.8583
Kinematic Viscosity @40°C, cSt	ASTM D7042	94.9
@100°C, cSt	ASTM D7042	14.1
Viscosity Index	ASTM D2270	152
Flash Point, °C, Min	ASTM D92	202
Pour Point, °C, Min	ASTM D97	-36
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	9.0