

DISTRIBUTED BY UMW GRANTT INTERNATIONAL SDN BHD (1103214-V) Jalan Utas 15/7, 40200 Shah Alam Selangor Darul Ehsan, Malaysia **T** +6 03 5163 5000 **F** +6 03 5519 0132

MANUFACTURED BY LUBETECH SDN BHD (096002-P)

www.granttlubricants.com

© UMWG (April 2019)







PREMIUM PRODUCT BY

UMW

PERFORMANCE FIRST Developed for immediate engine response for maximum performance





MINERAL



QUADRA RACING 4T SAE 10W-50

FOUR-STROKE MOTORCYCLE OIL

Grantt Quadra 4T Racing SAE 10W-50 is a fully synthetic oil with patented ester technology specially designed for all types of 4-stroke gasoline motorcycle engines including on road, high performance, four-cycle sport bikes and other type of 4-stroke cycle motorcycle which require SAE 10W-50 viscosity grade. It is suitable for use in both air-cooled and liquid-cooled engines.

BENEFITS

- · High shear stability provides viscosity retention at all riding conditions and helps to maintain power and longer engine life.
- · Its high lubricity helps to minimize friction, wear and tear in the engine.
- · High performance base oil technology offers excellent low emission, volatility control and longer drain intervals
- · Optimized wet-clutch performance.
- Excellent detergency to provide reliable protection, cleanliness and smoother-running engine.
- · Excellent seal compatibility.

GRADE: SAE 10W-50 · SPECIFICATIONS: API SN, JASO MA2 · PACK SIZE: 1L

SYNTHETIC BLEND



OUADRA 4T SAE 10W-40

FOUR-STROKE MOTORCYCLE OIL

GRANTT QUADRA 4T SAE 10W-40 is a premium four-stroke motorcycle oil formulated to provide exceptional engine protection and performance, even under the most extreme temperatures in high-speed riding conditions.

BENEFITS

- Optimized wet-clutch performance by reducing excess heat and friction.
- Excellent detergency to provide reliable protection, cleanliness and smoother-running engine.
- Reliable thermal and shear resistance to prevent oil thickening and piston deposits under high
- temperature conditions. · Helps prolong engine life.

GRADE: SAE 10W-40 · SPECIFICATIONS: API SM, JASO MA2 · PACK SIZE: 1L

MINERAL



QUADRA 4T SAE 15W-50 FOUR-STROKE MOTORCYCLE OIL

Grantt Quadra 4T SAE 15W-50 is designed for all types of 4-stroke gasoline motorcycle engines including on road, high performance, four-cycle sport bikes and other type of 4-stroke cycle motorcycles which require SAE 15W-50 viscosity grade. It is suitable for use in both air-cooled and liquid-cooled engines.

BENEFITS

- Thermally stable formula to maintain and protect engines under high RPMs and high temperature conditions.
- Enhanced anti-wear properties to reduce damaging wear and increased engine life.
- Offers excellent engine cleanliness, controlling sludge and engine deposits.
- Optimum friction control for maximum power transfer, smooth gear shifting, and better protection of the wet clutch.
- · JASO MA2 approval ensures that the oil will work perfectly with wet multi-disc clutches.

GRADE: SAE 15W-50 · SPECIFICATIONS: API SM, JASO MA2 · PACK SIZE: 1L



QUADRA 4T SAE 20W-40 FOUR-STROKE MOTORCYCLE OIL

GRANTT QUADRA 4T SAE 20W-40 is suitable for use in all Japanese and European 4-stroke motorcycles.

BENEFITS

- · Superior shear resistance due to high viscosity.
- Good protection against friction and wear of engine.
- Maintains engine cleanliness.

GRADE: SAE 20W-40 · SPECIFICATIONS: API SE/CC · PACK SIZE: 1L

MINERAL

120W-40@



QUADRA 4T SAE 40

FOUR-STROKE MOTORCYCLE OIL

GRANTT QUADRA 4T SAE 40 is suitable for use in all Japanese and European 4-stroke motorcycles.

BENEFITS

· Ensure superior deposits and minimized engine wear and tear.

- Provides excellent lubrication at all riding conditions.
- Good protection for engine, clutch and gears.
- · Maintains engine cleanliness.

GRADE: SAE 40 · SPECIFICATIONS: API SE/CC · PACK SIZE: 1L

MINERAL

GRANTT

QUADRA

21

QUADRA 2T TWO-STROKE MOTORCYCLE OIL

GRANTT QUADRA 2T is suitable for standard air-cooled 2 stroke engines.

BENEFITS

- Provides excellent lubrication at all riding conditions.
- Helps prolong engine life.
- Minimizes exhaust smoke.

GRADE: 2T · SPECIFICATIONS: API TA · PACK SIZE: 1L



• Excellent thermal and oxidation stability to ensure the best engine performance.

· Ensures superior deposits control to maintain engines cleanliness.