



AW GOLD HYDRAULIC OIL BUILT FOR PERFORMANCE







AW GOLD HYDRAULIC OIL ISO 32/46/68/100



GRANTT AW GOLD Hydraulic Oil can be used in a wide range of equipment such as hydraulic systems, heavy duty machineries, gear sets and other equipment requiring premium quality hydraulic oil. It is formulated and fortified with anti-wear, corrosion, oxidation and foam inhibitors to provide maximum protection required by both high and low pressure industrial hydraulic systems under severe applications. Its unique formulation ensures high resistance of oil thickening in service, excellent protection of machine surfaces against wear corrosion, thermal and oxidative stability as well as rust control.

BENEFITS:

- Excellent performance and anti-wear protection
- Copper Strip Corrosion Standard with 1A performance
- Good antifoam characteristics and rust protection
- High thermal and oxidation stability resulting in longer service life
- Improved filterability

PACK SIZE:

18 liters (pail/*jerry can) & 209 liters drum *GRANTT AW 68 Gold 18 liters is now available in jerry can

SPECIFICATIONS:

- Parker (Formerly Denison) HF-0, HF-1, HF-2(HM, HV)
- Eaton E-FDGN-TB002-E
- Fives P68, P69, P70 (HM, HV)
- DIN 51524-2 (HM), DIN 51524-3 (HV)
- SEB 181222

- ISO 11158 (HM, HV) **ASTM D6158 (HM, HV)**
- SAE MS 1004 (HM, HV)
- JCMAS P041 HK Hydraulic Specification
- GM LS-2
- AIST 126, 127

DISTRIBUTED BY:

UMW GRANTT INTERNATIONAL SDN. BHD.

201401027124 (1103214-V) Jalan Utas 15/7, 40200 Shah Alam Selangor Darul Ehsan, Malaysia

T+6 03 5163 5000

F+6 03 5519 0132

© UMWG (rev.1_Jan2020)

MANUFACTURED BY:

LUBETECH SDN. BHD.

198301000769 (96002-P)

www.granttlubricants.com