



Product Description

GRANTT STELLAR 8000 SAE 5W-40 is a fully synthetic motor oil with a unique formulation. It is engineered to provide ultimate protection against sludge formation and varnish deposits in the engine. This premium oil delivers exceptional resistance to high temperature oxidation thickening and outstanding cold-flow performance properties.

GRANTT STELLAR 8000 SAE 5W-40 is formulated with latest additive technology for extended wear performance, even under the most severe driving conditions. It also promotes extended oil drain intervals and engine life.

Application	GRANTT STELLAR 8000 SAE 5W-40 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel engine including fuel injected, turbocharged, conventional, multi-valve, naturally aspirated, LPG and NGV engine.
--------------------	---

Benefits	<ul style="list-style-type: none">• The formulation incorporates a highly stable viscosity index improver to offer promising viscosity control, high shear and high temperature protection• Exceptional performance motor oil for all season use• Ultimate protection during cold engine start-up• Maintains engine cleanliness
-----------------	--

Specifications

- API SN/CF
- ACEA A3/B4-04
- ACEA C3-10
- BMW Longlife-04
- MB 229.31
- PORSCHE A40
- VW 502 00 / 505 00
- RN 0700 / 0710

**Typical Properties**

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 5W-40
API Service Category		API SN/CF
Density @30°C, kg/l	ASTM D4052	0.8459
Kinematic Viscosity @40°C, cSt	ASTM D7042	85.7
@100°C, cSt	ASTM D7042	14.2
Viscosity Index	ASTM D2270	172
Flash Point, °C, Min	ASTM D92	220
Pour Point, °C, Min	ASTM D97	-39
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 6600 @ -30
Total Base Number, mgKOH/g	ASTM D2896	7.8