



Product Description

GRANTT STELLAR 5000 SAE 5W-30 is a synthetic blend motor oil. It is designed to provide excellent engine cleanliness for exceptional fuel efficiency, wear protection and performance.

GRANTT STELLAR 5000 SAE 5W-30 delivers outstanding resistance to temperature oxidation thickening and outstanding cold-flow performance properties. It offers extended wear protection, even under the most severe driving conditions.

Application	GRANTT STELLAR 5000 SAE 5W-30 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel engine including fuel injected, turbocharged, conventional, multi-valve, naturally aspirated, LPG and NGV engine.
--------------------	---

Benefits	<ul style="list-style-type: none">• Excellent engine wear protection in the most severe driving conditions• Helps prevent dirt and contamination from turning into performance robbing deposits• Maintains engine responsiveness• Excellent thermal and oxidation stability• Minimizes engine friction to offer fuel efficiency
-----------------	---

Specifications

- API SN/CF
- ILSAC GF-5

**Typical Properties**

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 5W-30
API Service Category		API SN/CF
Density @30°C, kg/l	ASTM D4052	0.8475
Kinematic Viscosity @40°C, cSt	ASTM D7042	59.6
@100°C, cSt	ASTM D7042	10.0
Viscosity Index	ASTM D2270	155
Flash Point, °C, Min	ASTM D92	218
Pour Point, °C, Min	ASTM D97	-36
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 6600 @ -30
Total Base Number, mgKOH/g	ASTM D2896	7.4