



## Product Description

---

GRANTT QUASAR SAE 40 is a high quality mono-grade diesel engine oil that provides superior protection against wear, deposits formation, rust and corrosion. It is formulated to deliver outstanding thermal and oxidation stability to maintain engine cleanliness.

<b>Application</b>	GRANTT QUASAR SAE 40 is suitable for heavy duty equipment for construction, mining and agriculture operations.
--------------------	--

<b>Benefits</b>	<ul style="list-style-type: none"><li>• Minimizes soot formation to maintain engine cleanliness.</li><li>• Protection against rust and corrosion.</li><li>• Superior thermal and oxidation stability.</li></ul>
-----------------	---

## Specifications

---

- API CF/CF-2/SF

**Typical Properties**

---

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 40
API Service Category		API CF/CF-2/SF
Density @30°C, kg/l	ASTM D4052	0.8785
Kinematic Viscosity @40°C, cSt	ASTM D7042	143.5
@100°C, cSt	ASTM D7042	14.3
Viscosity Index	ASTM D2270	97
Flash Point, °C	ASTM D92	230
Pour Point, °C	ASTM D97	-12
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	N/A
Total Base Number, mgKOH/g	ASTM D2896	6.6