

GRANTT SUPER TRACTOR OIL UNIVERSAL

SAE 15W-40



Product Description

GRANTT SUPER TRACTOR OIL UNIVERSAL (STOU) SAE 15W-40 is a reliable, premium multi-functional oil designed for use in tractor engine, transmission, hydraulic system, final drive and wet brake in most modern farm equipment. Proven STOU technology to meet all major manufacturer which provide an exceptional anti-wear performance and reliable frictional control to ensure smooth operations.

Application	GRANTT SUPER TRACTOR OIL UNIVERSAL SAE 15W-40 is suitable for most diesel and gasoline engines, transmission and hydraulic systems of tractors where manufacturers specify the use of STOU lubricants. It is also suitable for other applications of farm equipment's with powershift transmissions, CVTs and hydrostatic drives.
--------------------	---

Benefits	<ul style="list-style-type: none">• Extended wear and friction control leading to prolonged machine life, reduced downtime and improved performance.• Robust shear stability performance contributes to longer viscosity retention throughout fluid service life.• Versatility of formulation technology, one oil to lubricate all tractor components, reducing costly equipment failure due to misapplication.• Excellent protection against rust and oxidation.
-----------------	--

Typical Properties

Test	Method	Typical Results
Density @30°C, kg/l	ASTM D4052	0.8679
Kinematic Viscosity @40°C, cSt	ASTM D7042	110.7
@100°C, cSt	ASTM D7042	14.7
Viscosity Index	ASTM D2270	137
Flash Point, °C, Min	ASTM D92	222
Pour Point, °C, Min	ASTM D97	-39
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -20
Total Base Number, mgKOH/g	ASTM D2896	11.6

GRANTT SUPERTRACTOR OIL UNIVERSAL



SAE 15W-40

Specifications

Super Tractor Oil Universal

- ZF TE-ML 06A, 06B (Inc. 06R), 06C, 07B
- Ford M2C 159B
- Ford New Holland 82009201, 2, 3
- New Holland NH 030 C and NH 024 C
- Massey Ferguson: M1139, M1144 and M1145
- John Deere J27

Engine

- API CG-4
- API CF-4, CF, CE/SF, CD/SF
- ACEA E3
- MB 227.1, 228.1

Transmission/ UTTO

- API GL-4
- John Deere J20C, J20D
- Ford M2C86B, C
- Ford M2C134D
- J.I Case/Case Int: MS-1204,6,7,9
- CNH MAT 3525, 3526
- Massey Ferguson: M1139, M1144 and M1145
- Caterpillar TO-2
- Allison C-4

Hydraulic & Wet Brake

- Sperry Vickers/ Eaton:M2950S
- Sperry Vickers/ Eaton: I-280-S
- Sauer Sunstrand/ Danfoss: Hydrostatic TransFluid
- Suitable for Wet Brakes