

PREMIUM PRODUCT BY



**LUBRICANTS**

# AUTOMATIC TRANSMISSION OILS

OPTIMIZE VEHICLE PERFORMANCE  
WITH GRANTT



**Now AVAILABLE in 1 LITER  
NEW PACKAGING!**



LUBRICANTS

# GRANTT ATF MV & SP-III

FULLY SYNTHETIC



GRANTT ATF MULTI-VEHICLE & SP-III is a fully synthetic automatic transmission fluid designed for many modern automatic transmissions applications. It is formulated to provide the necessary wear protection, viscometric and frictional properties for use in a wide variety of Asian and North American vehicles.

It is fortified with high performance additives that offer anti-wear protection, shift quality, friction and oxidation stability, ultimate low and high temperature operation characteristics.

### BENEFITS

- Provides quiet operation and smooth shifting
- Excellent wear protection especially at low start-up temperature and maintains its properties at high operating temperature
- Resistant to high temperature oxidation and fluid thickening
- Provides protection against rust and corrosion

### PERFORMANCE STANDARD

- JASO M315 Type 1A
- Allison C-3/C-4
- Toyota Type T-III/T-IV (JWS 3309)
- Honda Z-1
- Mitsubishi SP-II/SP-III
- GM Dexron IIIH
- Ford Mercon
- Nissan Matic D/J/K
- Mazda ATF MIII, ATF MV

Suitable for PROTON and PERODUA transmissions where this type of fluids is recommended (except CVT models).

# GRANTT ATF DEXRON-III

SYNTHETIC BLEND

GRANTT ATF D-III is engineered and developed for use in all automatic transmission, power steering and other hydraulic systems where GM DEXRON III, Ford MERCON and Allison C-4 performance is required.

It is formulated to provide oxidation control, corrosion and wear protection, load-carrying ability, and friction stability.

### BENEFITS

- Smooth shifting performance where DEXRON III H or a MERCON fluid is specified
- Excellent friction, oxidation and thermal stability
- Excellent anti-corrosion and rust protection
- Excellent compatibility with seal materials

### PERFORMANCE STANDARD

- GM DEXRON III
- Ford MERCON
- Allison C-4

Suitable for PROTON and PERODUA transmissions where this type of fluids is recommended (except CVT models).



DISTRIBUTED BY

UMW GRANTT INTERNATIONAL SDN. BHD.  
201401027124 (1103214-V)

Jalan Utas 15/7, 40200 Shah Alam, Selangor Darul Ehsan, Malaysia  
Phone number: +603 5163 5000

MANUFACTURED BY

LUBETECH SDN. BHD.  
198301000769 (96002-P)

© UMWG (APRIL 2021)

MOVE FURTHER  
LAST LONGER™

umwgranttlube  
www.granttlubricants.com



PREMIUM PRODUCT BY



**LUBRICANTS**

# GEAR & TRANSMISSION OILS

OPTIMIZE VEHICLE PERFORMANCE WITH GRANTT

# MOVE FURTHER LAST LONGER™



DISTRIBUTED BY:  
**UMW GRANTT INTERNATIONAL SDN. BHD.**  
201401027124 (1103214-V)  
Jalan Utaş 15/7, 40200 Shah Alam  
Selangor Darul Ehsan, Malaysia  
Phone number: +603 5163 5000

MANUFACTURED BY:  
**LUBETECH SDN. BHD.**  
198301000769 (96002-P)



[umwgranttlube](https://www.umwgranttlube.com)

[www.granttlubricants.com](https://www.granttlubricants.com)


© UMWG (APRIL 2021)





## AUTOMATIC TRANSMISSION FLUID

### FULLY SYNTHETIC



### ATF CVT

GRANTT ATF CVT, formulated with specialized friction characteristic additives and premium grade fully synthetic base oil, is designed to meet and exceed the performance requirements of a wide variety of vehicles equipped with chain and belt for Continuous Variable Transmissions (CVT). Its superior technology helps to improve transmission efficiency, smoother drive and leading to longer transmission life.

#### PERFORMANCE STANDARD

Toyota CVTF (TC / FE), Mitsubishi CVTF-J1 / J4 / J4+ / SP-III, Mazda JWS 3320, Nissan NS-1, NS-2, NS-3, Hyundai / Kia (SP-III/J1), Suzuki (TC / NS-2 / CVT Green 1 / Green 1V / 3320), Daihatsu AMMIX CVTF DFE / DC / DFC / TC, Idemitsu CVTS-EX1, Subaru (iCVT / iCVT FG /ECVT / NS-2 / Lineartronic CVT / CVT II / HT), GM / Saturn (DEX-CVT), Mini Cooper EZL 799 /EZL 799A / ZF CVT V1, Audi / VW (TL 52180, G 052180 / TL 52116, G 052116), Audi Multitronic, Dodge / Jeep (NS-2 / CVTF+4), BMW Mini Cooper EZL 799/799A, Punch CVT, Shell Green 1V, Honda HCF2 / HMMF (without starting clutch) / Honda Z-1 (CVT model, without starting clutch) Not suitable for 2001-2007 Honda Fit & Jazz, Not recommended for Hybrid CVT unit (Toyota & Ford) - DCT Application

**PACK SIZE** 4L

#### BENEFITS

- Superior oil film / excellent shear stability helps to maintain oil pressure in the CVT system.
- Excellent extreme pressure and anti-wear extends transmission life longer.
- Good steel-to-steel frictional properties prevents chain and belt slippage thus extends transmission life.
- Superior high temperature protection prevents oxidation effectively.
- Outstanding transmission efficiency provides fuel economy and saves cost.



### ATF WS

GRANTT ATF WS is a fully synthetic transmission oil, specially designed with low viscosity formulation and balanced frictional properties to deliver excellent anti-shudder performance and smoother shifting. It has been tested for use in a wide range of modern Asian, North American and European vehicles. Exceeds the requirements of JASO 1A-LV performance.

#### PERFORMANCE STANDARD

JASO 1A-LV, Toyota ATF WS, Honda DW-1, Mitsubishi DiaQueen J3, Mazda ATF FZ, Nissan Matic Fluid S, Hyundai / Kia SP-IV, Hyundai i / Kia SP-IV M (SP4-M), Hyundai / Kia SP-IV-RR, Hyundai / Kia 040000C90SG, GM Dexron VI, BMW MINI, Chrysler / Dodge / Jeep 68043742AA, GM / GMC / Opel / Saturn (AW1 / 88863400 / 88863401), Jaguar ATF 3403 JLM20238 / ATF 3403 M115 / ATF LT71141 / ZF 5HP24, Saab 93 165 147, Volkswagen / Audi G 055 005 (A / A2), G 055 540 (A2), ZF 6 Speed Transmission

**PACK SIZE** 4L

#### BENEFITS

- Superior friction durability provide better anti-shudder performance.
- Excellent extreme pressure and anti-wear for better protection of transmission.
- Superior oxidation stability for longer fluid life and extended service interval.
- Superb seal compatibility prevents leakage.



### ATF MULTI-VEHICLE

GRANTT ATF MULTI-VEHICLE is a fully synthetic multifunctional fluid for automatic and power-shift transmissions. It is formulated for use in a wide variety of Asian, North American, and European vehicles.

#### PERFORMANCE STANDARD

JASO M315 Type 1A, Allison C-3/C-4, Honda Z-1, Toyota Type T-III/T-IV (JWS 3309), Ford Mercon, Mitsubishi SP-II/SP-III, GM Dexron IIIH, Nissan Matic D/J/K, Mazda ATF MIII, ATF MV

Suitable for PROTON and PERODUA transmissions where this type of fluids is recommended (except CVT models).

**PACK SIZE** 1L / 4L

#### BENEFITS

- Excellent lubricating characteristics for quiet operation and smooth shifting.
- Excellent wear protection especially at low start-up temperatures and maintains its properties at high operating temperatures.
- Resistant to high temperature oxidation and fluid thickening.
- Provides protection against rust and corrosion.

### SYNTHETIC BLEND



### ATF D-III

GRANTT ATF D-III is engineered and developed for use in all automatic transmissions, power steering and other hydraulic systems where GM DEXRON III H, Ford MERCON and Allison C-4 performance is required. It is also suitable for use in trucks and buses, off-highway construction, mining equipment, agricultural and industrial machineries.

#### PERFORMANCE STANDARD

GM DEXRON III H, Ford MERCON and Allison C-4

Suitable for PROTON and PERODUA transmissions where this type of fluids is recommended (except CVT models).

**PACK SIZE** 1L / 4L / 18L / 209L

#### BENEFITS

- Smooth shifting performance where GM DEXRON III H, Ford MERCON or Allison C-4 fluid is specified.
- Excellent friction, oxidation and thermal stability.
- Excellent corrosion, wear and rust protection.
- Excellent compatibility with seal materials.

## GEAR OIL

### MINERAL



### GEAR OIL SAE 90

GRANTT GEAR OIL SAE 90 is specially formulated to meet and exceed the requirements of API GL-4 service. It is fortified with extreme pressure additives for excellent protection of gear units, bearings and hypoid differentials which require API GL-4 performance.

#### PERFORMANCE STANDARD

API GL-4

**PACK SIZE** 4L / 18L / 209L

#### BENEFITS

- Heavy load carrying ability – the special high performance EP additives system that provides protection for gear surfaces.
- Outstanding thermal and oxidation stability.
- Excellent anti-corrosion and rust protection.



### GEAR OIL SAE 140

GRANTT GEAR OIL SAE 140 is specially formulated to meet and exceed the requirements of API GL-4 service. It is fortified with extreme pressure additives for excellent protection of gear units, bearings and hypoid differentials which require API GL-4 performance.

#### PERFORMANCE STANDARD

API GL-4

**PACK SIZE** 4L / 18L / 209L

#### BENEFITS

- Heavy load carrying ability – the special high performance EP additives system that provides protection for gear surfaces.
- Outstanding thermal and oxidation stability.
- Excellent anti-corrosion and rust protection.