



## Product Description

---

GRANTT QUASAR SAE 15W-40 is a high quality diesel engine motor oil that delivers advanced lubricant performance and excellent detergency to control deposits and varnish formation on critical engine components thus helps optimize engine durability.

<b>Application</b>	GRANTT QUASAR SAE 15W-40 is suitable for four wheel drives (4WD), sport utility vehicles (SUVs), light-heavy duty trucks and heavy duty machineries and equipment in construction, mining and agriculture.
--------------------	--

<b>Benefits</b>	<ul style="list-style-type: none"><li>• Excellent soot control and maintains engine cleanliness</li><li>• Ultimate engine wear protection</li><li>• Excellent thermal and oxidation stability</li></ul>
-----------------	---

## Specifications

---

- API CF-4/SG

**Typical Properties**

---

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 15W-40
API Service Category		API CF-4/SG
Density @30°C, kg/l	ASTM D4052	0.8638
Kinematic Viscosity @40°C, cSt	ASTM D7042	103.6
@100°C, cSt	ASTM D7042	13.8
Viscosity Index	ASTM D2270	133
Flash Point, °C, Min	ASTM D92	205
Pour Point, °C, Min	ASTM D97	-33
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -20
Total Base Number, mgKOH/g	ASTM D2896	7.9