

GRANTT STELLAR 1000 SAE 10W-30



Product Description

GRANTT STELLAR 1000 SAE 10W-30 is premium mineral motor oil. It is designed to provide excellent engine cleanliness for exceptional fuel efficiency, wear protection and performance.

GRANTT STELLAR 1000 SAE 10W-30 is engineered to offer extra performance and protection against the harmful effects of combustion, high and low temperature in the most severe driving conditions.

Application	GRANTT STELLAR 1000 SAE 10W-30 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel.
--------------------	---

Benefits	<ul style="list-style-type: none">• Excellent engine lubrication under extreme conditions and maintain engines responsiveness• Reliable thermal and oxidation stability• Maintains engine cleanliness• Optimizes engine wear protection and help prolong engine life• Low viscosity oil to offer better fuel efficiency
-----------------	---

Specification

- API SN



Typical Properties

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-30
API Service Category		API SN
Density @30°C, kg/l	ASTM D4052	0.8566
Kinematic Viscosity @40°C, cSt	ASTM D7042	76.2
@100°C, cSt	ASTM D7042	11.5
Viscosity Index	ASTM D2270	144
Flash Point, °C, Min	ASTM D92	216
Pour Point, °C, Min	ASTM D97	-30
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	7.7