

PREMIUM PRODUCT BY



LUBRICANTS

HYDRAULIC OIL



PREMIUM SERIES

AW GOLD ISO 32 / 46 /68/ 100

GRANTT AW GOLD Hydraulic Oil can be used in a wide range of equipment such as hydraulic systems, heavy duty machineries, gear sets and other equipment requiring premium quality hydraulic oil. It is formulated and fortified with anti-wear, corrosion, oxidation and foam inhibitors to provide maximum protection required by both high and low pressure industrial hydraulic systems under severe applications. Its unique formulation ensures high resistance of oil thickening in service, excellent protection of machine surfaces against wear corrosion, thermal and oxidative stability as well as rust control.

BENEFITS:

- Excellent performance and anti-wear protection
- Copper Strip Corrosion Standard with 1A performance
- Good antifoam characteristics and rust protection
- High thermal and oxidation stability resulting in longer service life
- Improved filterability

SPECIFICATIONS:

- Parker (Formerly Denison) HF-0, HF-1, HF-2(HM, HV)
- Eaton E-FDGN-TB002-E
- Fives P68, P69, P70 (HM, HV)
- DIN 51524-2 (HM), DIN 51524-3 (HV)
- SEB 181222
- ISO 11158 (HM, HV)
- ASTM D6158 (HM, HV)
- SAE MS 1004 (HM, HV)
- JCMAS P041 HK Hydraulic Specification
- GM LS-2
- AIST 126, 127

PACK SIZE:

18 liters (pail/*jerry can) & 209 liters drum

**GRANTT AW 68 Gold is now available in 18 liters jerry can*

SUPER SERIES

ISO 68

GRANTT HYD68 is a super mineral-based hydraulic oils with good oxidation stability and outstanding protection against rust and corrosion in the most demanding of systems while still meeting ISO standards for hydraulic oil. The quality of anti-wear and anti-foam additive package prevents wear of internal components and facilitates the rapid release of entrained air, therefore maximizing hydraulic system efficiency.

BENEFITS:

- Good anti-wear protection to extend components life
- Good antifoam characteristics to ensure smooth operation
- Resistance to oxidation to prolong oil life
- Good water separation

SPECIFICATION:

- ISO VG 68

PACK SIZE:

209 liters drum

DISTRIBUTED BY:

UMW GRANTT INTERNATIONAL SDN. BHD.

201401027124 (1103214-V)

Jalan Utas 15/7, 40200 Shah Alam

Selangor Darul Ehsan, Malaysia

Phone number: +603 5163 5000

MANUFACTURED BY:

LUBETECH SDN. BHD.

198301000769 (96002-P)

**MOVE FURTHER
LAST LONGER**

     [umwgranttlube](https://umwgranttlube.com)

 <https://granttlubricants.com>