



Product Description

GRANTT STELLAR 1000 SAE 10W-40 is premium mineral motor oil. The unique additive technology reduces friction and wear at start-up, providing superior protection against sludge formation and varnish deposits under the most severe driving conditions.

GRANTT STELLAR 1000 SAE 10W-40 is designed to deliver excellent thermal and oxidation stability for longer oil drain interval, thus minimizing oil thickening at high operating temperature.

Application	GRANTT STELLAR 1000 SAE 10W-40 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel engine including fuel injected, turbocharged, conventional, multi-valve, naturally aspirated, LPG and NGV engine.
--------------------	--

Benefits	<ul style="list-style-type: none">• Excellent engine lubrication under extreme conditions and maintain engines responsiveness• Reliable thermal and oxidation stability• Maintains engine cleanliness• Optimizes engine wear protection and help prolong engine life
-----------------	---

Specifications

- API SN/CF

**Typical Properties**

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-40
API Service Category		API SN/CF
Density @30°C, kg/l	ASTM D4052	0.8658
Kinematic Viscosity @40°C, cSt	ASTM D7042	93.8
@100°C, cSt	ASTM D7042	13.9
Viscosity Index	ASTM D2270	152
Flash Point, °C, Min	ASTM D92	220
Pour Point, °C, Min	ASTM D97	-30
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	7.1