

GRANTT QUASAR SAE 10W



Product Description

GRANTT QUASAR SAE 10W is a high quality mono-grade diesel engine oil that provides superior protection which reduces soot formation and offers rust and corrosion protection on critical engine components.

| | |
|--------------------|---|
| Application | GRANTT QUASAR SAE 10W is suitable for transmission and mobile hydraulic system, heavy duty equipment for construction, mining and agriculture operations. |
|--------------------|---|

| | |
|-----------------|---|
| Benefits | <ul style="list-style-type: none">• Minimizes engine wear under severe operating conditions.• Maintains engine cleanliness.• Protection against rust and corrosion. |
|-----------------|---|

Specifications

- API CF-4/SG



Typical Properties

| Test | Method | Typical Results |
|--|------------|-----------------|
| SAE Viscosity Grade | J300 | SAE 10W |
| API Service Category | | API CF-4/SG |
| Density @30°C, kg/l | ASTM D4052 | 0.8704 |
| Kinematic Viscosity @40°C, cSt | ASTM D7042 | 36.9 |
| @100°C, cSt | ASTM D7042 | 6.2 |
| Viscosity Index | ASTM D2270 | 114 |
| Flash Point, °C, Min | ASTM D92 | 210 |
| Pour Point, °C, Min | ASTM D97 | -27 |
| Low Temperature Viscosity (cP) at Temperature (°C), Max | ASTM D5293 | MAX 7000 @ -25 |
| Total Base Number, mgKOH/g | ASTM D2896 | 7.7 |