GRANTT QUADRA 4T SAE 40



Product Description

GRANTT QUADRA 4T SAE 40 is a specially designed for four-stroke motorcycle oil to protect against harmful sludge and varnish deposits. It is formulated to resist viscosity breakdown at high temperatures.

Enhanced with highly refined mineral base oil and versatile additives package to provide good lubrication for engine cleanliness, superior anti-wear properties and oil film thickness even in the most severe speed and load conditions.

Application	GRANTT QUADRA 4T SAE 40 is suitable for use in all Japanese and European 4-stroke motorcycles.
-------------	--

 Ensure superior deposits and minimized engine wear and tear. Provides excellent lubrication at all riding conditions. Good protection for engine, clutch and gears. Maintains engine cleanliness. 	
--	--

Specifications

API SG/CD

GRANTT QUADRA 4T SAE 40



Typical Properties

Test	Method	Typical Results
API Service Category		API SG/CD
Density @30°C, kg/l	ASTM D4052	0.8883
Kinematic Viscosity		
@40°C, cSt	ASTM D7042	132.5
@100°C, cSt	ASTM D7042	13.6
Viscosity Index	ASTM D2270	97
Flash Point, °C, Min	ASTM D92	210
Pour Point, °C, Min	ASTM D97	-9
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	NA
Total Base Number, mgKOH/g	ASTM D2896	6.5