



Product Description

GRANTT ATF D-III is engineered and developed for use in all automatic transmission, power steering and other hydraulic systems where GM DEXRON III, Ford MERCON and Allison C-4 performance is required. It is formulated to provide oxidation control, corrosion and wear protection, load-carrying ability, and friction stability.

Application	GRANTT ATF D-III is recommended for use in all automatic transmissions that reference specifications GM DEXRON III, Ford MERCON and Allison C-4. It is also suitable for use in light and heavy duty trucks, buses, on and off-highway vehicles, mining equipment, agricultural, industrial machinery, power steering units and hydraulic system where fluid of this type are recommended.
--------------------	--

Benefits	<ul style="list-style-type: none">• Smooth shifting performance where DEXRON III H or a MERCON fluid is specified.• Excellent friction, oxidation and thermal stability.• Excellent anti-corrosion and rust protection.• Excellent compatibility with seal materials.
-----------------	--

Specifications

- GM DEXRON III, Ford MERCON and Allison C-4

**Typical Properties**

Test	Method	Typical Results
Colour	Vision	Red
Density @30°C, kg/l	ASTM D4052	0.8471
Kinematic Viscosity @40°C, cSt	ASTM D7042	39.1
@100°C, cSt	ASTM D7042	7.8
Viscosity Index	ASTM D2270	175
Flash Point, °C, Min	ASTM D92	212
Pour Point, °C, Min	ASTM D97	- 42