GRANTT STELLAR 1000 SAE 10W-30



Product Description

GRANTT STELLAR 1000 SAE 10W-30 is premium mineral motor oil. It is designed to provide excellent engine cleanliness for exceptional fuel efficiency, wear protection and performance.

GRANTT STELLAR 1000 SAE 10W-30 is engineered to offer extra performance and protection against the harmful effects of combustion, high and low temperature in the most severe driving conditions.

Application	GRANTT STELLAR 1000 SAE 10W-30 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel.
-------------	---

Specification

API SN

GRANTT STELLAR 1000 SAE 10W-30



Typical Properties

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-30
API Service Category		API SN
Density @30°C, kg/l	ASTM D4052	0.8566
Kinematic Viscosity		
@40°C, cSt	ASTM D7042	76.2
@100°C, cSt	ASTM D7042	11.5
Viscosity Index	ASTM D2270	144
Flash Point, °C, Min	ASTM D92	216
Pour Point, °C, Min	ASTM D97	-30
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	7.7