

GRANTT STELLAR 8000 SAE 5W-30



Product Description

GRANTT STELLAR 8000 SAE 5W-30 is a fully synthetic motor oil with a unique formulation. It is engineered to provide ultimate protection against sludge formation and varnish deposits in the engine. These premium oils deliver exceptional resistance to high temperature oxidation thickening and outstanding cold-flow performance properties.

GRANTT STELLAR 8000 SAE 5W-30 is formulated with latest additive technology for extended wear performance, even under the most severe driving conditions. It also promotes extended oil drain intervals and engine life.

| | |
|--------------------|---|
| Application | GRANTT STELLAR 8000 SAE 5W-30 is suitable for all American, European and Japanese passenger cars fitted with modern gasoline or light duty diesel engine including fuel injected, turbocharged, conventional, multi-valve, naturally aspirated, LPG and NGV engine. |
|--------------------|---|

| | |
|-----------------|--|
| Benefits | <ul style="list-style-type: none">• The formulation incorporates a highly stable viscosity index improver to offer promising viscosity control, high shear and high temperature protection• Exceptional performance motor oil for all season use• Ultimate protection during cold engine start-up• Keeps engine cleanliness |
|-----------------|--|

Specifications

- API SN
- ACEA C3
- MB 229.31
- MB 229.51

**Typical Properties**

| Test | Method | Typical Results |
|--|------------|-----------------|
| SAE Viscosity Grade | J300 | SAE 5W-30 |
| API Service Category | | API SN/CF |
| Density @30°C, kg/l | ASTM D4052 | 0.8447 |
| Kinematic Viscosity @40°C, cSt | ASTM D7042 | 66.2 |
| @100°C, cSt | ASTM D7042 | 11.7 |
| Viscosity Index | ASTM D2270 | 174 |
| Flash Point, °C, Min | ASTM D92 | 218 |
| Pour Point, °C, Min | ASTM D97 | -39 |
| Low Temperature Viscosity (cP) at Temperature (°C), Max | ASTM D5293 | MAX 6600 @ -30 |
| Total Base Number, mgKOH/g | ASTM D2896 | 7.3 |