GRANTT QUASAR SAE 15W-40



Product Description

GRANTT QUASAR SAE 15W-40 is a high quality diesel engine motor oil that delivers advanced lubricant performance and excellent detergency to control deposits and varnish formation on critical engine components thus helps optimize engine durability.

Application	GRANTT QUASAR SAE 15W-40 is suitable for four wheel drives (4WD), sport utility vehicles (SUVs), light-heavy duty trucks and heavy duty machineries and equipment in construction, mining and agriculture.
-------------	--

Benefits	 Excellent soot control and maintains engine cleanliness Ultimate engine wear protection Excellent thermal and oxidation stability
----------	---

Specifications

• API CF-4/SG

GRANTT QUASAR SAE 15W-40



Typical Properties

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 15W-40
API Service Category		API CF-4/SG
Density @30°C, kg/l	ASTM D4052	0.8638
Kinematic Viscosity		
@40°C, cSt	ASTM D7042	103.6
@100°C, cSt	ASTM D7042	13.8
Viscosity Index	ASTM D2270	133
Flash Point, °C, Min	ASTM D92	205
Pour Point, °C, Min	ASTM D97	-33
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -20
Total Base Number, mgKOH/g	ASTM D2896	7.9