GRANTT QUADRA 4T 15W-50 SEMI SYN



Product Description

GRANTT QUADRA 4T 15W-50 SEMI SYN is a premium semi synthetic engine oil designed for four-stroke motorcycles that demand API SP performance levels. Formulated with a powerful combination of advanced additives and high-quality base oils, it delivers excellent protection under extreme temperatures, high RPM, and heavy load conditions.

Engineered for superior resistance to volatility, this oil prevents the buildup of harmful sludge and carbon deposits, ensuring exceptional engine cleanliness. It is ideal for a wide range of applications, including modern fuel-injected motorcycles, high-performance bikes, and big bikes that require extra protection. It meets JASO requirements, ensuring excellent clutch compatibility and performance.

Application

GRANTT QUADRA 4T 15W-50 SEMI SYN is designed for all types of 4-stroke gasoline motorcycle engines including on road, high performance, four-cycle sport bikes and other types of 4-stroke cycle motorcycles which require SAE 15W-50 viscosity grade. It is suitable for use in both air-cooled and liquid-cooled engines.

Benefits

- Thermally stable formula to maintain and protect engines under high RPMs and high temperature conditions.
- Enhanced anti-wear properties to reduce damaging wear and increased engine life.
- Offers excellent engine cleanliness, controlling sludge and engine deposits.
- Optimum friction control for maximum power transfer, smooth gear shifting, and better protection of the wet clutch.

Specifications

- API SP
- JASO MA2

GRANTT QUADRA 4T 15W-50 SEMI SYN



Typical Properties

Test	Method	Typical Results
API Service Category		API SP
Density @30°C, kg/l	ASTM D4052	0.8687
Kinematic Viscosity		
@40°C, cSt	ASTM D7042	133.6
@100°C, cSt	ASTM D7042	17.87
Viscosity Index	ASTM D2270	149
Flash Point, °C, Min	ASTM D92	200
Pour Point, °C, Min	ASTM D5950	-27
Low Temperature Viscosity (cP) at		
Temperature (°C), Max	ASTM D5293	6486
Total Base Number, mgKOH/g	ASTM D2896	8.0